

## TSC-DP

### NON-REFRIGERATED CURVED GLASS DISPLAY CASE

#### DESCRIPTION OF STANDARD UNIT:

- 2 versions: DRY (DP), refrigerated (RP).
- Construction of powder coated steel
- Finishes in stainless steel or powder coated steel
- Double front, and side glass with PCV finishing
- Perforated stainless steel back panel
- Highlighted (LED) and adjustable stainless still shelves
- Controller on the front or back
- Tempered glass
- Forced cooling
- Temp. range\*: room temperature
- Front opening glass

#### OPTIONS:

- Refrigerated version
- Multiplexing
- Version for external condensing unit
- Stainless steel shelves & base decks
- Light plafond
- Night blind
- Wheels




SPECIFICATIONS					
MODEL	LENGTH	DEPTH	HEIGHT	WEIGHT (LBS / KG)	ELECTRICAL
TSC2-DP	23 5/8"	29 1/2"	54 3/4"	198 / 90	115V / 60Hz / 1ph / 8 AMP
TSC3-DP	35 1/2"		54 3/4"	253 / 115	115V / 60Hz / 1ph / 9.5 AMP
TSC4-DP	47 1/4"		54 3/4"	330 / 150	115V / 60Hz / 1ph / 11.5 AMP



\* Temperature range given for maximum ambient temperature of +25°C and relative humidity 60%.  
 \*\* Cooling power demand: 1500 W/1mr at evaporating temp. -10°C. Automatic water evaporation on request.  
 \*\*\* In version with doors: only top lighting

#### Wood Stains



#### Available Colors

