

RF-2SWDP

LOW VERSION - 2 SHELVES

NON-REFRIGERATED STRAIGHT FRONT GLASS DISPLAY CASE

DESCRIPTION OF STANDARD UNIT:

- Non-refrigerated version.
- LED lighting
- Construction of powder coated steel
- Wooden casing
- Side and front glasses: double with serigraph (golden, silver or black)
- 2 rows of highlighted adjustable shelves: glass (RF-R, RF-D) or stainless steel (RF-H)
- Sliding, double glass rear doors (except RF2 - hinged glass doors)
- Forced cooling
- Temp. range* room temperature
- Front opening glass
- Front glass secured by string cable




OPTIONS:

- Refrigerated version
- For external condensing unit
- Wheels
- Ultrasonic humidifier (except RF 2)
- Stainless steel worktop
- Thermometer in the lamp
- For individual decoration
- Multiplexing
- Highlighted front
- Glass on top worktop

* - Values are provided for an ambient temp of +25°C and relative humidity of 60%.
 ** - Cooling power demand: 1000 W/1mr at evaporating temp. -10°C.


SPECIFICATIONS					
MODEL	LENGTH	DEPTH	HEIGHT	WEIGHT (LBS / KG)	ELECTRICAL
RF2-2SWDP	25 1/4"	33 3/4"	46"	253 / 115	115V / 60Hz / 1ph / 2 AMP
RF3-2SWDP	37"	33 3/4"	46"	374 / 170	115V / 60Hz / 1ph / 2 AMP
RF4-2SWDP	51 1/4"	33 3/4"	46"	485 / 220	115V / 60Hz / 1ph / 3 AMP



Profile Colors



Wood Stains



Available Colors



154 Norfinch Dr, Unit 5 - 6, North York, Ont, M3N 1X6 | TEL: 416-665-0095 | TOLL FREE: 877-265-0095

info@frosttechrefrigeration.com | www.frosttechrefrigeration.com

